

Brookewood Clic

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" 152.4mm x 914.4mm
Overall Thickness*	1/6" / 4.0mm
Wearlayer	6 mil / 0.15mm - Also features a top wear layer that has superior scratch and stain resistance qualities.
Construction	Layered plank consisting of wearlayer, film and backing.
Edge	4-sided Square
Standard Colors	2 standard colors
Installation Method	Click floating utilizing unilin locking system.
Wear Limited Warranty	10-Year Residential
Recycled Content	This product contains recycled content. 100% recyclable post-use.
Packaging	6" x 36" 22.79 ft² (2.12 m²) per carton 16 pieces per carton 50 cartons per pallet 18 pallets per 20' container
Weight Per Carton	42.5lbs / 19.28kg

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.